

**model 30 - 34**

**Push-Type Grease Gun  
made of shock-resistant polyamide**



form B acc. to DIN 1282  
suitable  
for hydraulic,  
ball-type, and flush-type nipples



barrel version  
suitable for  
connection thread  
packaging

shock-resistant polyamide gun body  
grease up to NLGI2  
M 9 x 1  
bulk

technical datas	Type 30	Type 34
filling capacity	60 ccm (2.0 oz.)	150 ccm (5.1 oz.)
operating pressure (approx.)	80-120 bar (1,160-1,740 PSI)	80-120 bar (1,160-1,740 PSI)
delivery capacity per stroke	0.6 ccm (0.02 oz.)	0.6 ccm (0.02 oz.)
total length	165 mm (6 1/2")	200 mm (7 7/8")
tube measurements Ø x L	30 x 105 mm (1.18" x 4.13")	42 x 140 mm (1.66" x 5.5")
weight	62 g (2.2 oz.)	100 g (3.5 oz.)

Type	connection M 9 x 1	ref. no.:
<b>30</b>	hollow-type nozzle 500	7130433
<b>30/S</b>	pointed nozzle 500/S	7130133
<b>30/H</b>	hydraulic nozzle 500/H	7130233
<b>30/NS</b>	pin pointed nozzle 500/NS	7130533
<b>30/K</b>	combi nozzle 500/K	7133933
<b>34</b>	hollow-type nozzle 500	7134433
<b>34/S</b>	pointed nozzle 500/S	7134133
<b>34/H</b>	hydraulic nozzle 500/H	7134233
<b>34/NS</b>	pin pointed nozzle 500/NS	7134533
<b>34/K</b>	combi nozzle 500/K	7135933