

## model 40 - 44



### Telescopic Push-Type Grease Gun made of shock-resistant polyamide

- form A acc. to DIN 1282
- with telescopic tube
- suitable for hydraulic, ball-type, and flush-type nipples



barrel version  
suitable for  
connection thread  
packaging

shock-resistant polyamide gun body  
grease up to NLGI 2  
M 9 x 1  
loose

	Type 40	Type 42	Type 44
filling capacity bulk grease	70 ccm (2.4 oz.)	110 ccm (3.7 oz.)	180 ccm (6.1 oz.)
operating pressure (approx.)	140 bar / 2,030 PSI	180 bar / 2,610 PSI	200 bar / 2,900 PSI
output per stroke	0.8 - 1.2 ccm (0.03-0.04 oz.)	0.8 - 1.2 ccm (0.03-0.04 oz.)	0.8 - 1.2 ccm (0.03-0.04 oz.)
total length	240 mm (9 1/2")	270 mm (10 1/2")	335 mm (13 1/2")
tube measurements in mm (Ø x L)	36 x 100 (0.42" x 3.94")	41 x 110 (1.62" x 4.33")	45 x 135 (1.78" x 5.31")
weight	100 g (3.5 oz.)	120 g (4.25 oz.)	150 g (5.3 oz.)

type	connection M 9 x 1	ref. no.:
40	hollow-type nozzle 500	7140433
40/S	pointed nozzle 500/S	7140133
40/H	hydraulic nozzle 500/H	7140233
40/NS	pin pointed nozzle 500/NS	7140333
40/K	combi nozzle 500/K	7140533
42	hollow-type nozzle 500	7142433
42/S	pointed nozzle 500/S	7142133
42/H	hydraulic nozzle 500/H	7142233
42/NS	pin pointed nozzle 500/NS	7142533
42/K	combi nozzle 500/K	7142733
44	hollow-type nozzle 500	7144433
44/S	pointed nozzle 500/S	7144133
44/H	hydraulic nozzle 500/H	7144233
44/NS	pin pointed nozzle 500/NS	7144533
44/K	combi nozzle 500/K	7144753