

■ UMETA Grease Gun, foot operated grease pump



*special coupler
for hands-free operating*

Ref. No.:

1/8" BSP 9626836

M 10 x 1 9626837

for heavy duty, industrial strength that allows for hands-free and waste-free operation, mainly in the outdoor area.

The unique two stage pump creates a wave action that smooths out those annoying airlocks.

Grease will be supplied up to the end of the canister, no follower plate is necessary.

Therefore you will be independent from special bucket sizes, dirty and messed followerplates are history!

- Portable with comfortable carry handle
- Foot operated treadle with pressure release!
When lifting the treadle, the pressure return valve is activated and grease flows back into the canister
- Two Stage Pump with pressure return valve returns grease under pressure into the bucket. Easy and undangerous disconnection of coupler and hose - recovers from airlocks
- Fitted with high pressure hose, min. burst pressure 1,600 bar (23,200 PSI) special coupler for hands-free and mess-free greasing
- The big sized bucket (8 KG, 282 oz) is suited for many greasing points - no change of cartridges necessary
- All steel parts are powder coated for longlife operation, even outside

Technical Details at a glance:

| | |
|--------------------------------------|---|
| output | 3 ccm (0,10 oz)/stroke |
| operating pressure | up to 690 bar (10,000 PSI) |
| filling capacity | 8 KG (282 oz.) bulk grease |
| flexible hose with standard fittings | length 2m (6.5ft) with special coupler G-136 (M10 x 1) and hose parking high pressure up to 1,600 bar |
| all steel parts | powdercoated |
| packed in | single carton box |

| Scope of delivery | Ref. No.: |
|---|-----------|
| with 2m hose and special coupler G-136, (M10 x 1) | 9626835 |