

# INJECTION GUNS

UMETA Hand lever injection guns for sealing and pressing works, specially well for building reconstruction. Viton-sealings allow for cleaning with solvents and for multi-use. The different tube lengths make the filling volume up to 1,100 ccm (35.0 oz.) possible.



## 75/PKI Zinc



barrel version	made of zinc-plated steel
	Ø 56 mm (2.2")
barrel length	295 mm
suitable	for resin
filling capacity	550 ccm (17.5 Oz.) bulk grease
connection thread	M 10 x 1 or G 1/8
	upon request 1/8 NPT

## Injection gun

- for 550 ccm (17.5 oz.) filling material
- with rolled, zinc-plated steel cap

operating pressure	400 bar / 5,800 PSI
output	approx. 1.9 ccm (0.06 oz.)/stroke
testing pressure	800 bar / 11,600 PSI
packed in	polybag
weight	960 g (33.9 oz.)
	+ accessories and packaging
dimensions (L x W x H)	356 x 125 x 67.5 mm (14.0 x 4.9 x 2.6")

Connection	Packed in	Scope of delivery	Ref. No.:
M 10 x 1	polybag	without accessories	7091156

Connection	Packed in	Scope of delivery	Ref. No.:
G 1/8	polybag	without accessories	7091157

**75/PKI Zinc**



barrel version made of zinc-plated steel  
 Ø 56 mm (2.2")  
 barrel length 296 mm  
 suitable for resin  
 filling capacity 550 ccm (17.5 Oz.) bulk grease  
 connection thread M 10 x 1 or G 1/8, upon request 1/8 NPT

Connection	Packed in	Scope of delivery	Ref. No.:
M 10 x 1	polybag	without accessories	V000334

**Injection gun**

- für 550 ccm (17.5 oz.) filling material
- with orange polyamide cap

operating pressure 400 bar / 5,800 PSI  
 output approx. 1.9 ccm (0.06 Oz.)/stroke  
 testing pressure 800 bar / 11,600 PSI  
 packed in polybag  
 weight 960 g (33.9 oz.) + accessories and packaging  
 dimensions (L x W x H) 356 x 125 x 67.5 mm (14.0 x 4.9 x 2.6")

Connection	Packed in	Scope of delivery	Ref. No.:
G 1/8	polybag	without accessories	V001440

**75/LLI Zinc**



barrel version made of zinc-plated steel  
 Ø 56 mm (2.2")  
 barrel length 485 mm  
 suitable for resin  
 filling capacity 1,100 ccm (35 oz.) bulk material  
 connection thread M 10 x 1 or G 1/8, upon request 1/8 NPT

Connection	Packed in	Scope of delivery	Ref. No.:
M 10 x 1	polybag	without accessories	V000340

**Injection gun**

- long version for 1,100 ccm (35 oz.) filling material
- with orange polyamide cap

operating pressure 400 bar / 5,800 PSI  
 output approx. 1.9 ccm (0.06 Oz.)/stroke  
 testing pressure 800 bar / 11,600 PSI  
 packed in polybag  
 weight 1,230 g (43.4 oz.) + accessories and packaging  
 dimensions (L x W x H) 545 x 125 x 67.5 mm (21.5 x 4.9 x 2.6")

Connection	Packed in	Scope of delivery	Ref. No.:
G 1/8	polybag	without accessories	V001478

**75/LLI Zinc**



barrel version made of zinc-plated steel  
 Ø 56 mm (2.2")  
 barrel length 453 mm  
 suitable for resin  
 filling capacity 1,000 ccm (32 oz.) bulk grease  
 connection thread M 10 x 1 or G 1/8, upon request 1/8 NPT

Connection	Packed in	Scope of delivery	Ref. No.:
M 10 x 1	polybag	without accessories	7091312

**Injection gun**

- long version for 1,000 ccm (32 oz.) filling material
- with zinc-plated steel screw cap

operating pressure 400 bar / 5,800 PSI  
 output approx. 1.9 ccm (0.06 Oz.)/stroke  
 testing pressure 800 bar / 11,600 PSI  
 packed in polybag  
 weight 1,260 g (44.4 oz.) + accessories and packaging  
 dimensions (L x W x H) 513 x 125 x 67.5 mm (20.2 x 4.9 x 2.6")

Connection	Packed in	Scope of delivery	Ref. No.:
G 1/8	polybag	without accessories	upon request